



Gate Repair Services

0114633025 0834522015

www.gates.co.za



Separate
control
unit

ET Blue Roll-Up

Features:

- Low battery warning indication
- Soft start & Stop feature
- Separate control housing
- Courtesy light
- Electronic locking feature
- Easy to program
- Additional safety features
- Adjustable load setting
- Compatible with ET rolling code receiver
- Left or right hand fitment
- Ideal for limited space
- Mechanical limits with easy access
- Anti-crush feature
- Auto close feature

Technical specification	ET BLUE ROLL-UP
Input voltage: (Standard kit option)	230v AC, 50Hz-60Hz
Primary supply to the electric motor:	24V Toroidal transformer. Not battery dependent.
Maximum duty cycle with mains present:	25%*
Number of operations on battery reserve without AC mains present:	20 within the first 24h of power failure**
Maximum door size:	8m ²
Applicable door types:	One-piece Aluzinc or Cromadek roll-up doors
Maximum running load:	400N**
Rated speed:	9.6m/min (Drum speed)†
Built-in receiver:	434MHz, ET BLUE™ rolling code. 25 button capacity

* At rated running load

** Battery charge level and health dependent

† Dependent on factors such as battery status, door load, mains voltage, environment etc

• Technical specifications subject to change

For Gate Motor and Intercom Repairs, or Quotes on New Installations

Call the National Call Centre 011 463 3025 today

24 hour emergency 083 452 2015

repairs@gates.co.za / www.gates.co.za