



XTrac

DOMESTIC SECTIONAL AND TIP-UP GARAGE DOOR OPERATORS

Main features

- Novel operating principal and revolutionary design
- Dual power - ALWAYS on, with battery backup
- Reliable DC motor
- Adaptive anti-crushing control
- Whisper quiet movement
- Adjustable speed giving you ultimate control
- Manual override and lock in any position
- Autoclose - with safety beams fitted, the XTrac can remember to close the door for you
- Onboard, ultra secure NOVA receiver
- Quick and easy installation
- Door service monitor
- Wireless wall pendant to operate all of the functions
- Smooth ramp up and ramp down
- Power supply flexibility
- Energy saving technology

Models

XTrac - Quiet, Safe and reliable garage door operator for majority of sectional and tip-up doors.

Close Technical Details

XTrac's Technical Data

Data	Description
Input voltage	180 – 270V AC @ 50/60Hz ^Ω
Motor voltage	24V DC
Motor power supply	Dual supply – 250VA max. mains power supply, with 2 X 1.5AH 24V battery backup supply ‡
Opener lifting force – max	1200N
Operator travel speed	90-125mm/sec (adjustable)
Duty cycle - mains present ^Ω	20% ^ϕ
Daily operations - max	20
Maximum door size	12m ² – (max width 6.5m)
Onboard receiver specification	NOVA rolling code ‡, single channel, 433MHz, with 22 transmitter buttons capacity

^Ω - Can operate off a solar supply, consult Centurion Systems for assistance

‡ - 2 x 1.5AH batteries (can be upgraded for longer power failure autonomy)

^ϕ - Based on 25°C ambient temperature

^Ω - Based on a pull force of less than 50% of rated

‡ - Keeloq™ encryption

National Call Center 011 463 3025

For gate motor and intercom repairs
Call 011 463 3025 today
24 hour emergency 083 452 2015